

View Online at <https://aerobasegroup.com/nsn/5930-00-276-7600>

Thread Length:

0.375 inches single mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

4.050 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.210 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.750 inches single actuator

Overall Diameter:

2.000 inches

Nonturn Device Radius:

0.372 inches at 12: 00 o'clock

Individual Section Quantity:

7

Nonturn Device Type:

Tab at 12: 00 o'clock

Operating Temperature Range:

-54.0/+55.0 degrees celsius

Mounting Method:

Threaded bushing single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.469 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

180.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

12 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Switch Actuator Positioning Increment:

15.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

200.0 milliamperes resistive load dc at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A052b0