

View Online at <https://aerobasegroup.com/nsn/5930-00-279-2897>

Hazardous Locations/environmental Protection:

Dustproof and weatherproof

Overall Length:

1.313 inches

Overall Height:

0.594 inches

Overall Width:

0.400 inches

Mounting Slot Width:

0.112 inches

Body Length:

0.750 inches

Body Width:

0.344 inches

Body Height:

0.344 inches

Distance Between Mounting Facility Centers:

1.031 inches

Temperature Sensing Element Type:

Internal sensor

Operating Temperature Rating:

125.0 degrees celsius and -65.0 degrees celsius

Mounting Method:

Bracket and slot

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

5.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

+0.00/+300.00 actuation point degrees fahrenheit and +0.00/+300.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Stimulus Rating:

220.00 actuation point degrees fahrenheit and 216.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Frequency In Hertz:

60.0 first voltage and 400.0 first voltage

Media For Which Designed:

Gas or liquid

Precious Material And Location:

Case surface gold

Precious Material:

Gold

Style Designator:

Rectangular w/bracket

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0