

View Online at <https://aerobasegroup.com/nsn/5930-00-279-2897>

**Hazardous Locations/environmental Protection:**

Dustproof and weatherproof

**Overall Length:**

1.313 inches

**Overall Height:**

0.594 inches

**Overall Width:**

0.400 inches

**Mounting Slot Width:**

0.112 inches

**Body Length:**

0.750 inches

**Body Width:**

0.344 inches

**Body Height:**

0.344 inches

**Distance Between Mounting Facility Centers:**

1.031 inches

**Temperature Sensing Element Type:**

Internal sensor

**Operating Temperature Rating:**

125.0 degrees celsius and -65.0 degrees celsius

**Mounting Method:**

Bracket and slot

**Features Provided:**

Hermetically sealed case

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally closed, momentary action

**Terminal Type:**

Tab, solder lug

**Contact Load Current Rating:**

5.0 amperes resistive load second voltage

**Contact Adjustability:**

Deactuation point adjustable, preset and actuation point adjustable, preset

**Contact Adjustment Range:**

+0.00/+300.00 actuation point degrees fahrenheit and +0.00/+300.00 deactuation point degrees fahrenheit

**Contact Adjustment Type:**

External deactuation point screw and external actuation point screw

**Contact Stimulus Rating:**

220.00 actuation point degrees fahrenheit and 216.00 deactuation point degrees fahrenheit

**Contact Voltage Rating In Volts:**

28.0 dc at sea level second voltage

**Frequency In Hertz:**

60.0 first voltage and 400.0 first voltage

**Media For Which Designed:**

Gas or liquid

**Precious Material And Location:**

Case surface gold

**Precious Material:**

Gold

**Style Designator:**

Rectangular w/bracket

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0