

View Online at <https://aerobasegroup.com/nsn/5930-00-287-8905>

Thread Length:

0.594 inches single mounting facility

Overall Length:

1.938 inches

Overall Height:

1.188 inches

Overall Width:

1.188 inches

Flat Height:

0.216 inches single actuator

Shaft Length:

1.000 inches single actuator

Nonturn Device Radius:

0.375 inches at 12: 00 o'clock

Individual Section Quantity:

2

Nonturn Device Type:

Tab at 12: 00 o'clock

Operating Temperature Range:

-65.0/+125.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 each section rear

Throw Quantity:

6 each section front

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

180.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

6 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

500.0 milliamperes resistive load dc at sea level

Special Features:

Selected item drawing

Precious Material And Location:

Contact surfaces silver

Style Designator:

Square wafer, panel mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0