NSN 5930-00-295-2945

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-295-2945

| Body Style: |
|---|
| Panel mounted |
| Overall Length: |
| 3.022 inches |
| Overall Height: |
| Between 1.190 inches and 1.210 inches |
| Overall Width: |
| Between 0.950 inches and 0.970 inches |
| Body Width: |
| Between 0.950 inches and 0.970 inches |
| Body Height: |
| 1.200 inches |
| Case Material: |
| Metal |
| Actuator Length: |
| 1.035 inches |
| Actuator Style: |
| Rectangular |
| Actuator Height: |
| 0.188 inches |
| Actuator Width: |
| 0.735 inches |
| Actuator Color: |
| White single actuator |
| Illuminated Actuator Color: |
| White single actuator |
| Actuator Inscription: |
| Abnormal single actuator |
| Maximum Voltage Rating In Volts: |
| 30.0 dc |
| End Application: |
| An/gpn-12 |
| Mounting Surface To Terminal End Distance: |
| 2.812 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Panel |
| Features Provided: |
| Full display lens |
| Nonpile-up Contact Arrangement: |
| 2 pole, double throw, one position momentary single switch unit |

NSN 5930-00-295-2945

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

5 tab, solder lug and 6 turret

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0