## NSN 5930-00-296-3916



Lever Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-00-296-3916 **Body Style:** Hole mounted **Overall Length:** 5.687 inches Center To Center Distance Between Mounting Facilities Parallel To Width: 0.624 inches **Overall Width:** 1.312 inches **Body Width:** 1.312 inches **Body Height:** 1.750 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.250 inches **Actuator Style:** Round **Actuator Height:** 1.562 inches **Actuator Position-action Relationship:** Up position maintained and down position maintained and center position maintained **Actuator Position-locking Relationship:** Up position locked in and down position locked in and center position locked in **Actuator Color:** Black single actuator **Maximum Voltage Rating In Volts:** 110.0 ac

**Inclosure Type:** Uninclosed

**Mounting Method:** 

Unthreaded hole

Thready Qty Per Inch (tpi):

**Pile-up Contact Form Arrangement:** 

1a 2nd position

**Thread Size:** 

0.112 inches

**Contact Load Current Rating At Maximum Rated Voltage:** 

10.000 amperes resistive ac

**Special Features:** 

Silver contacts moisture and fungus proof

**Thread Series Designator:** 

Unc

## NSN 5930-00-296-3916

Lever Switch - Page 2 of 2



i ei ii ii iai Tybe And Quantity.	Tε	rminal	Type	And	Quantity:	
-----------------------------------	----	--------	------	-----	-----------	--

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0