## NSN 5930-00-296-4222

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-296-4222

Thread Class:
2a single pressure connection
Inside Diameter:
0.125 inches single connection
Overall Length:
4.062 inches
Overall Width:
3.625 inches
Body Diameter:
3.000 inches
Body Length:
2.531 inches
Unthreaded Mounting Hole Diameter:
Between 0.195 inches and 0.200 inches
Distance Between Mounting Facility Centers:
3.000 inches
Pressure Switch Type:
Gage
Mounting Method:
Bracket and unthreaded hole
Features Provided:
Electrical access port
Thready Qty Per Inch (tpi):
27 single pressure connection
Contact Action Stimulus:
Increase
Thread Size:
0.125 inches single pressure connection
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Connector, receptacle
Contact Load Current Rating:
2.0 amperes resistive load single voltage
Contact Adjustability:
Deactuation point not adjustable and actuation point not adjustable
Contact Stimulus Rating:
23.00 actuation point, inches of water and 17.00 deactuation point, inches of water and 6.00 differential point, inches of water

Contact Voltage Rating In Volts: 30.0 dc at sea level single voltage

## NSN 5930-00-296-4222

Pressure Switch - Page 2 of 2



Pressure Connector Type:
Plain, threaded internal single connection
Media For Which Designed:
Gas
Style Designator:
Cylindrical w/mounting lugs
Thread Series Designator:
Npt single pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0