NSN 5930-00-296-4222

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-296-4222

Thread Class:

2a single pressure connection

Inside Diameter:

0.125 inches single connection

Overall Length:

4.062 inches

Overall Width:

3.625 inches

Body Diameter:

3.000 inches

Body Length:

2.531 inches

Unthreaded Mounting Hole Diameter:

Between 0.195 inches and 0.200 inches

Distance Between Mounting Facility Centers:

3.000 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

27 single pressure connection

Contact Action Stimulus:

Increase

Thread Size:

0.125 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

2.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

23.00 actuation point inches of water and 17.00 deactuation point inches of water and 6.00 differential point inches of water

Contact Voltage Rating In Volts:

30.0 dc at sea level single voltage

NSN 5930-00-296-4222

Pressure Switch - Page 2 of 2



Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Gas

Style Designator:

Cylindrical w/mounting lugs

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A048b0