

View Online at <https://aerobasegroup.com/nsn/5930-00-296-4226>

Thread Class:

2a single pressure connection

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

6.625 inches

Overall Height:

4.125 inches

Overall Width:

4.125 inches

Distance Between Mounting Facility Centers:

3.357 inches

Pressure Switch Type:

Gage

Mounting Method:

Flush

Features Provided:

Calibrated scale

Thready Qty Per Inch (tpi):

20 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

200.00 pounds per square inch

Thread Size:

0.438 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, both positions maintained

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

5.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

55.00 actuation point pounds per square inch and 40.00 deactuation point pounds per square inch

Contact Voltage Rating In Volts:

30.0 dc at sea level second voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Liquid

Style Designator:

Rectangular

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A048b0