NSN 5930-00-296-4309

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-296-4309

view Online at https://aerobasegroup.com/nsn/5930-00-296-4309
Hazardous Locations/environmental Protection:
Watertight
Overall Height:
7.125 inches
Overall Width:
7.125 inches
First Flat Length:
0.500 inches single actuator
Flat Height:
0.310 inches single actuator
Shaft Diameter:
0.375 inches single actuator
Unthreaded Mounting Hole Diameter:
0.406 inches single mounting facility
Individual Section Quantity:
4
Knob Manufacturer Code:
80064
Knob Manufacturer Part Number:
9000s6202-74276
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 each section front
Throw Quantity:
2 each section front
Mounting Facility Circle Radius:
3.312 inches single mounting facility
Mounting Method:
Base single mounting facility
Features Provided:
Actuator knob and metallic inclosure
Contact Voltage Rating In Volts:
500.0 ac at sea level
Switch Actuator Momentary Position:
Clockwise single actuator and counterclockwise single actuator
Mounting Facility Pattern:
Three position circular single mounting facility
Switch Actuator Indexing Position Quantity:
4 single actuator
Shaft Tyne:

Shaft Type:

Round, flatted single actuator

NSN 5930-00-296-4309 Rotary Switch - Page 2 of 2



Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes each section front
Switch Actuator Positioning Increment:
90.0 degrees single actuator
Contact Load Current Rating:
30.0 amperes resistive load dc at sea level
Specification Or Standard:
3sr4c4-2 type
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A052b0