NSN 5930-00-296-4362

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-296-4362

Thread Class: 2a single mounting facility Thread Length: 0.250 inches single mounting facility **Overall Length:** 1.159 inches **Overall Height:** 1.313 inches **Overall Width:** 1.094 inches **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 0.500 inches single actuator **Nonturn Device Radius:** 0.531 inches at 12: 00 o'clock **Individual Section Quantity:** 1 **Nonturn Device Type:** Tab at 12: 00 o'clock **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 2 single section front **Throw Quantity:** 1 single section front **Mounting Method:** Threaded bushing single mounting facility **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 400.0 dc at sea level **Switch Actuator Indexing Position Quantity:** 1 single actuator **Shaft Type:** Round single actuator **Terminal Type:** Tab, solder lug **Contact Switching Action:** Breaks before makes single section front **Switch Actuator Positioning Increment:**

30.0 degrees single actuator

NSN 5930-00-296-4362

Rotary Switch - Page 2 of 2



Detent Rotational Torque Range:

+4.000/+8.000 inch-ounces single actuator

Contact Load Current Rating:

500.0 milliamperes resistive load dc at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0