NSN 5930-00-296-4420

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-296-4420

Thread Class: 2a single mounting facility Thread Length: 0.375 inches single mounting facility **Hazardous Locations/environmental Protection:** Dustproof **Overall Length:** 2.266 inches **Overall Height:** 1.719 inches **Overall Width:** 1.719 inches **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 0.500 inches single actuator **Individual Section Quantity:** 1 **Knob Manufacturer Code:** 76572 **Switch Contact Basic Design:** Pile-up **Mounting Method:** Threaded bushing single mounting facility **Features Provided:** Cam actuated **Pile-up Contact Form Arrangement:** 2b 2nd switch single section in-line **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 110.0 ac at sea level **Switch Actuator Indexing Position Quantity:** 3 single actuator **Shaft Type:** Round single actuator **Terminal Type:** Tab, solder lug **Contact Switching Action:** Makes before breaks single section front

Switch Actuator Positioning Increment:

45.0 degrees single actuator

NSN 5930-00-296-4420

Rotary Switch - Page 2 of 2



Switch Actuator Stop Device Type: Fixed stop single actuator **Contact Load Current Rating:** 5.0 amperes resistive load ac at sea level **Precious Material And Location:** Contacts palladium **Precious Material:** Palladium Style Designator: In-line, pile-up, bushing mount **Thread Series Designator:** Unef single mounting facility Shelf Life: N/a **Unit Of Measure:** Demilitarization:

No Fiig: A052b0