

View Online at <https://aerobasegroup.com/nsn/5930-00-296-4420>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.375 inches single mounting facility

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

2.266 inches

**Overall Height:**

1.719 inches

**Overall Width:**

1.719 inches

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.500 inches single actuator

**Individual Section Quantity:**

1

**Knob Manufacturer Code:**

76572

**Switch Contact Basic Design:**

Pile-up

**Mounting Method:**

Threaded bushing single mounting facility

**Features Provided:**

Cam actuated

**Pile-up Contact Form Arrangement:**

2b 2nd switch single section in-line

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

110.0 ac at sea level

**Switch Actuator Indexing Position Quantity:**

3 single actuator

**Shaft Type:**

Round single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Makes before breaks single section front

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

5.0 amperes resistive load ac at sea level

**Precious Material And Location:**

Contacts palladium

**Precious Material:**

Palladium

**Style Designator:**

In-line, pile-up, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0