# NSN 5930-00-296-4430

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-296-4430

## **Thread Class:**

2a single mounting facility

## Thread Length:

0.250 inches single mounting facility

## **Overall Length:**

1.812 inches

#### **Overall Height:**

1.875 inches

#### **Overall Width:**

1.625 inches

#### First Flat Length:

0.250 inches single actuator

### Flat Height:

0.188 inches single actuator

#### Shaft Diameter:

0.250 inches single actuator

# Shaft Length:

0.750 inches single actuator

## Individual Section Quantity:

1

Switch Contact Basic Design:

Nonpile-up symmetrical

## **Pole Quantity:**

1 single section front

### **Throw Quantity:**

4 single section front

### **Mounting Method:**

Threaded bushing single mounting facility

### **Thread Size:**

0.375 inches single mounting facility

### Contact Voltage Rating In Volts:

28.0 dc at sea level

### Switch Actuator Indexing Position Quantity:

4 single actuator

### Shaft Type:

Round, flatted single actuator

### **Terminal Type:**

Tab, solder lug

### **Contact Switching Action:**

Breaks before makes single section front

# Switch Actuator Positioning Increment:

30.0 degrees single actuator

# NSN 5930-00-296-4430

Rotary Switch - Page 2 of 2



Switch Actuator Stop Device Type:

Fixed stop single actuator

**Contact Load Current Rating:** 

1.0 amperes resistive load ac at sea level

**Precious Material And Location:** 

Contacts and rotor blade surfaces silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0