

View Online at <https://aerobasegroup.com/nsn/5930-00-296-4868>

Overall Length:

5.000 inches

Overall Width:

0.625 inches

Body Diameter:

Between 0.618 inches and 0.625 inches

Body Length:

3.531 inches

Longest Horizontal Distance Between Mounting Centers:

Between 1.079 inches and 1.085 inches

Shortest Horizontal Distance Between Mounting Centers:

Between 0.536 inches and 0.546 inches

Longest Vertical Distance Between Mounting Centers:

Between 0.827 inches and 0.947 inches

Temperature Sensing Element Type:

Internal sensor

Mounting Method:

Flange and threaded hole

Thready Qty Per Inch (tpi):

32 all threaded hole

Contact Action Stimulus:

Increase

Thread Size:

0.164 inches all threaded hole

Mounting Facility Pattern:

Isosceles triangle

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Wire lead

Contact Load Current Rating:

5.0 amperes resistive load first voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

-50.00/+400.00 actuation point degrees fahrenheit and -50.00/+400.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Stimulus Rating:

350.00 actuation point degrees fahrenheit and 340.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

230.0 ac at sea level first voltage

Special Features:

One 1.750 in. Diameter mtg flange supplied

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Unc all threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0