

View Online at <https://aerobasegroup.com/nsn/5930-00-296-4874>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Humidity resistant

Actuator Style:

Round

Actuator Height:

Between 1.165 inches and 1.175 inches

Actuator Free Position Height:

3.734 inches

Housing Height:

Between 1.025 inches and 1.035 inches

Housing Length:

Between 1.745 inches and 1.755 inches

Housing Width:

Between 1.995 inches and 2.005 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

Between 1.370 inches and 1.380 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

Between 1.620 inches and 1.630 inches

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

Inclosure Type:

Hermetically sealed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary single switch unit

Switch Release Force:

1.0 ounces

Switch Actuating Force:

Between 2.0 ounces and 4.0 ounces

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 10.000 amperes resistive ac

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0