

View Online at <https://aerobasegroup.com/nsn/5930-00-296-4874>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Humidity resistant

**Actuator Style:**

Round

**Actuator Height:**

Between 1.165 inches and 1.175 inches

**Actuator Free Position Height:**

3.734 inches

**Housing Height:**

Between 1.025 inches and 1.035 inches

**Housing Length:**

Between 1.745 inches and 1.755 inches

**Housing Width:**

Between 1.995 inches and 2.005 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Length:**

Between 1.370 inches and 1.380 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Width:**

Between 1.620 inches and 1.630 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 30.0 dc

**Inclosure Type:**

Hermetically sealed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 two circuit, double break/double make, one position momentary single switch unit

**Switch Release Force:**

1.0 ounces

**Switch Actuating Force:**

Between 2.0 ounces and 4.0 ounces

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive dc and 10.000 amperes resistive ac

**Terminal Type And Quantity:**

4 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0