

View Online at <https://aerobasegroup.com/nsn/5930-00-296-5136>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.990 inches and 1.010 inches

**Overall Height:**

1.656 inches

**Overall Width:**

0.688 inches

**Body Length:**

Between 1.922 inches and 1.954 inches

**Body Width:**

Between 0.672 inches and 0.704 inches

**Body Height:**

Between 1.015 inches and 1.079 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

Between 0.139 inches and 0.142 inches

**Actuator Length:**

Between 1.886 inches and 1.916 inches

**Actuator Style:**

Roller arm

**Actuator Free Position Height:**

Between 1.396 inches and 1.416 inches

**Actuator Roller Diameter:**

Between 0.359 inches and 0.391 inches

**Actuator Roller Width:**

Between 0.140 inches and 0.172 inches

**Maximum Voltage Rating In Volts:**

460.0 ac and 250.0 dc

**Inclosure Type:**

Fully enclosed

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

0.8 ounces

**Switch Actuating Force:**

3.5 ounces

**Actuator Movement:**

Between 0.250 pretravel inches and 0.140 overtravel inches and 0.078 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

**Terminal Type And Quantity:**

3 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0