

View Online at <https://aerobasegroup.com/nsn/5930-00-296-5136>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.990 inches and 1.010 inches

Overall Height:

1.656 inches

Overall Width:

0.688 inches

Body Length:

Between 1.922 inches and 1.954 inches

Body Width:

Between 0.672 inches and 0.704 inches

Body Height:

Between 1.015 inches and 1.079 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

Between 0.139 inches and 0.142 inches

Actuator Length:

Between 1.886 inches and 1.916 inches

Actuator Style:

Roller arm

Actuator Free Position Height:

Between 1.396 inches and 1.416 inches

Actuator Roller Diameter:

Between 0.359 inches and 0.391 inches

Actuator Roller Width:

Between 0.140 inches and 0.172 inches

Maximum Voltage Rating In Volts:

460.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

0.8 ounces

Switch Actuating Force:

3.5 ounces

Actuator Movement:

Between 0.250 pretravel inches and 0.140 overtravel inches and 0.078 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0