NSN 5930-00-296-5145



Sensitive Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-00-296-5145 **Thread Class:** 2a **Body Style:** Bushing/hole mounted **Overall Length:** 1.930 inches **Center To Center Distance Between Mounting Facilities Parallel To Length:** 1.000 inches **Overall Height:** 2.221 inches **Overall Width:** 0.688 inches **Body Length:** 1.930 inches **Body Width:** 0.688 inches **Body Height:** 0.820 inches **Case Material:** Plastic **Unthreaded Mounting Hole Diameter:** 0.140 inches **Actuator Style:** Roller plunger **Actuator Free Position Height:** 1.281 inches **Actuator Roller Diameter:** 0.500 inches **Actuator Roller Width:** 0.190 inches **Maximum Voltage Rating In Volts:** 600.0 ac and 250.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded bushing **Thread Size:**

0.500 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

4.0 ounces

NSN 5930-00-296-5145

Sensitive Switch - Page 2 of 2



Switch Actuating Force	∌:
------------------------	----

Between 9.0 ounces and 13.0 ounces

Actuator Movement:

Between 0.020 pretravel inches and 0.140 overtravel inches and 0.003 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 2.000 amperes resistive ac

Thread Series Designator:

Unf

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A053a0