## NSN 5930-00-296-5209

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-296-5209

**Thread Class:** 

2b single mounting facility

**Overall Length:** 

1.969 inches

**Shaft Diameter:** 

0.250 inches single actuator

**Shaft Length:** 

0.594 inches single actuator

**Overall Diameter:** 

1.750 inches

**Individual Section Quantity:** 

1

## **Longest Horizontal Distance Between Mounting Centers:**

1.062 inches single mounting facility

## **Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:** 

1 single section front

**Throw Quantity:** 

2 single section front

**Mounting Method:** 

Threaded hole single mounting facility

Thready Qty Per Inch (tpi):

40 single mounting facility

**Thread Size:** 

0.112 inches single mounting facility

**Contact Voltage Rating In Volts:** 

115.0 ac at sea level

**Mounting Facility Pattern:** 

Two position in-line single mounting facility

**Switch Actuator Indexing Position Quantity:** 

3 single actuator

**Shaft Type:** 

Round single actuator

Terminal Type:

Tab, solder lug

**Contact Switching Action:** 

Breaks before makes single section front

**Switch Actuator Positioning Increment:** 

60.0 degrees single actuator

**Switch Actuator Stop Device Type:** 

Fixed stop single actuator

## NSN 5930-00-296-5209

Rotary Switch - Page 2 of 2



Contact	Load	Current	Rating:
---------	------	---------	---------

1.0 amperes resistive load ac at sea level

**Style Designator:** 

Circular wafer, bushing mount

**Thread Series Designator:** 

Unc single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0