

View Online at <https://aerobasegroup.com/nsn/5930-00-296-5290>

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

3.406 inches

Overall Diameter:

4.375 inches

Unthreaded Mounting Hole Diameter:

0.375 inches single mounting facility

Individual Section Quantity:

3

Knob Manufacturer Code:

10001

Knob Manufacturer Part Number:

9000-s6202-74000 piece 1

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Facility Circle Radius:

0.625 inches single mounting facility

Mounting Method:

Unthreaded hole single mounting facility

Features Provided:

Actuator knob and metallic inclosure

Contact Voltage Rating In Volts:

120.0 ac at sea level

Mounting Facility Pattern:

Three position circular single mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

10.0 amperes resistive load ac at sea level

Style Designator:

Tap, circular, bushing mount

Test Data Document:

81349-mil-s-15743 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-s-15743/3 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0