## NSN 5930-00-296-5290

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-296-5290

Hazardous Locations/environmental Protection:
Watertight
Overall Length:
3.406 inches
Overall Diameter:
4.375 inches
Unthreaded Mounting Hole Diameter:
0.375 inches single mounting facility
Individual Section Quantity:
3
Knob Manufacturer Code:
10001
Knob Manufacturer Part Number:
9000-s6202-74000 piece 1
Switch Contact Basic Design:
Nonpile-up nonsymmetrical
Mounting Facility Circle Radius:
0.625 inches single mounting facility
Mounting Method:
Unthreaded hole single mounting facility
Features Provided:
Actuator knob and metallic inclosure
Contact Voltage Rating In Volts:
120.0 ac at sea level
Mounting Facility Pattern:
Three position circular single mounting facility
Switch Actuator Indexing Position Quantity:
4 single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes each section front
Switch Actuator Positioning Increment:
90.0 degrees single actuator
Contact Load Current Rating:
10.0 amperes resistive load ac at sea level
Style Designator:
Tap, circular, bushing mount
Test Data Document:

81349-mil-s-15743 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-s-15743/3 government specification

## NSN 5930-00-296-5290

Rotary Switch - Page 2 of 2



-				
٠.	hΔ	Iŧ.	ife:	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0