## NSN 5930-00-296-5814

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-296-5814

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Dustproof
Actuator Length:
1.562 inches
Actuator Style:
Roller arm
Actuator Roller Diameter:
0.750 inches
Actuator Roller Width:
0.312 inches
Housing Height:
1.670 inches
Housing Length:
4.060 inches
Housing Width:
1.000 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
3.250 inches
Maximum Voltage Rating In Volts:
480.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Actuating Force:
80.0 ounces
Actuator Movement:
Between 0.008 pretravel inches and 0.203 overtravel inches and 0.004 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
250.000 milliamperes resistive dc and 15.000 amperes resistive ac
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

## NSN 5930-00-296-5814

Sensitive Switch - Page 2 of 2



Fiig:

A053a0