## NSN 5930-00-296-5826

Sensitive Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-296-5826

Maximum Voltage Rating In Volts:
250.0 ac
Inclosure Type:
Fully enclosed
Thready Qty Per Inch (tpi):
32
Thread Size:
0.138 inches
Nonpile-up Contact Arrangement:
1 pole, double throw, both positions maintained single switch unit
Switch Release Force:
35.0 ounces
Switch Actuating Force:
35.0 ounces
Actuator Movement:
Between 0.200 pretravel inches and 0.156 overtravel inches and 0.400 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
Contact Load Gurrent Rating At Maximum Rated Voltage.
7.500 amperes resistive ac
7.500 amperes resistive ac
7.500 amperes resistive ac  Thread Series Designator:
7.500 amperes resistive ac  Thread Series Designator: Unc
7.500 amperes resistive ac  Thread Series Designator: Unc  Terminal Type And Quantity:
7.500 amperes resistive ac  Thread Series Designator: Unc  Terminal Type And Quantity: 3 tab, solder lug
7.500 amperes resistive ac  Thread Series Designator: Unc  Terminal Type And Quantity: 3 tab, solder lug  Shelf Life:
7.500 amperes resistive ac  Thread Series Designator: Unc  Terminal Type And Quantity: 3 tab, solder lug  Shelf Life: N/a
7.500 amperes resistive ac  Thread Series Designator: Unc  Terminal Type And Quantity: 3 tab, solder lug  Shelf Life: N/a
7.500 amperes resistive ac  Thread Series Designator: Unc  Terminal Type And Quantity: 3 tab, solder lug  Shelf Life: N/a  Unit Of Measure:
7.500 amperes resistive ac  Thread Series Designator: Unc  Terminal Type And Quantity: 3 tab, solder lug  Shelf Life: N/a Unit Of Measure: Demilitarization:
7.500 amperes resistive ac Thread Series Designator: Unc Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No
7.500 amperes resistive ac  Thread Series Designator: Unc  Terminal Type And Quantity: 3 tab, solder lug  Shelf Life: N/a Unit Of Measure: Demilitarization: No  Fiig: