

View Online at <https://aerobasegroup.com/nsn/5930-00-296-5845>

Thread Class:

2a

Body Style:

Bushing mounted

Overall Length:

1.031 inches

Body Diameter:

0.562 inches

Bushing Length:

0.250 inches

Body Length:

0.425 inches

Actuator Diameter:

0.312 inches

Actuator Height:

0.188 inches

Actuator Color:

Black single actuator

Maximum Voltage Rating In Volts:

230.0 ac and 24.0 dc

End Application:

Helicopter, search and rescue; hh-60j, hh-60h; helicopter, carrier based asw, sh-60f; spruance class dd (963); support equipment, mx peacemaker missile; deepsubmergence systems programs (dssp); kidd class ddg; seawolf class ssn

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.500 inches

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

17.000 amperes resistive dc and 7.500 amperes resistive ac

Special Features:

Weapon system essential

Thread Series Designator:

Un

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0