

View Online at <https://aerobasegroup.com/nsn/5930-00-296-6023>

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

18.366 inches

**Overall Height:**

8.000 inches

**Overall Width:**

8.000 inches

**First Flat Length:**

0.866 inches single actuator

**Shaft Diameter:**

0.625 inches single actuator

**Shaft Length:**

0.625 inches single actuator

**Individual Section Quantity:**

25

**Knob Manufacturer Code:**

80064

**Knob Manufacturer Part Number:**

9-s-5564-l-19

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

2 each section front

**Throw Quantity:**

8 each section front

**Mounting Facility Circle Radius:**

7.000 inches single mounting facility

**Mounting Method:**

Bracket single mounting facility

**Features Provided:**

Actuator knob and metallic inclosure

**Thready Qty Per Inch (tpi):**

24 single mounting facility

**Thread Size:**

0.190 inches single mounting facility

**Contact Voltage Rating In Volts:**

125.0 ac at sea level

**Shaft Flat/slot Angular Location:**

22.5 degrees from contact position 1 single actuator

**Mounting Facility Pattern:**

Four position circular single mounting facility

**Switch Actuator Indexing Position Quantity:**

8 single actuator

**Shaft Type:**

Round, square single actuator

**Square Shaft Size:**

0.375 inches single actuator

**Terminal Type:**

Tab w/screw

**Contact Switching Action:**

Breaks before makes each section front

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Adjustable stop single actuator

**Contact Load Current Rating:**

10.0 amperes resistive load ac at sea level

**Special Features:**

6-32 threaded hole located on vertical axis of shaft

**Style Designator:**

Tap, circuit selector

**Test Data Document:**

80064-9-s-5568-I drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Thread Series Designator:**

Unc single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0