

View Online at <https://aerobasegroup.com/nsn/5930-00-296-6039>

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

10.438 inches

Overall Height:

6.750 inches

Overall Width:

6.750 inches

Unthreaded Mounting Hole Diameter:

0.266 inches single mounting facility

Individual Section Quantity:

6

Knob Manufacturer Code:

80064

Knob Manufacturer Part Number:

9000s6503-73437pc37

Longest Horizontal Distance Between Mounting Centers:

5.812 inches single mounting facility

Shortest Horizontal Distance Between Mounting Centers:

2.906 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

6.125 inches single mounting facility

Shortest Vertical Distance Between Mounting Centers:

3.062 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

16 each section front

Mounting Method:

Base single mounting facility and unthreaded hole single mounting facility

Features Provided:

Actuator knob and metallic inclosure

Contact Voltage Rating In Volts:

120.0 ac at sea level

Mounting Facility Pattern:

Four position diamond single mounting facility

Switch Actuator Indexing Position Quantity:

16 single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

22.5 degrees single actuator

Contact Load Current Rating:

10.0 amperes resistive load ac at sea level

Style Designator:

Tap, circuit selector

Specification Or Standard:

Js6c16b type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0