

View Online at <https://aerobasegroup.com/nsn/5930-00-296-6161>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

4.250 inches

Overall Width:

3.125 inches

Body Diameter:

3.000 inches

Unthreaded Mounting Hole Diameter:

0.203 inches

Distance Between Mounting Facility Centers:

3.000 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 160.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Automatic reset

Contact Action Stimulus:

Increase

Proof Pressure:

75.00 pounds per square inch

Thread Size:

0.438 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

2.0 amperes resistive load single voltage

Contact Adjustability:

Actuation point not adjustable

Contact Stimulus Rating:

8.00 actuation point pounds per square inch

Contact Voltage Rating In Volts:

30.0 dc at sea level single voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical w/mounting lugs

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0