

View Online at <https://aerobasegroup.com/nsn/5930-00-296-6201>

**Overall Length:**

5.438 inches

**Overall Height:**

1.320 inches

**Overall Width:**

3.090 inches

**Body Length:**

3.250 inches

**Body Height:**

2.530 inches

**Unthreaded Mounting Hole Diameter:**

0.203 inches

**Distance Between Mounting Facility Centers:**

2.750 inches

**Pressure Switch Type:**

Differential

**Operating Temperature Rating:**

Between -65.0 degrees fahrenheit and 100.0 degrees fahrenheit

**Mounting Method:**

Flush and unthreaded hole

**Thready Qty Per Inch (tpi):**

32 single pressure connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

4500.00 pounds per square inch

**Thread Size:**

0.375 inches single pressure connection

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Sensing Element Burst Pressure:**

7500.00 pounds per square inch

**Terminal Type:**

Connector, receptacle

**Contact Load Current Rating:**

5.0 amperes inductive load single voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

2850.00 deactuation point pounds per square inch and 200.00 differential point pounds per square inch and 3050.00 actuation point pounds per square inch

**Contact Voltage Rating In Volts:**

28.0 dc at altitude single voltage

**Pressure Connector Type:**

Flared, threaded external single connection

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular

**Thread Series Designator:**

Unef single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0