

View Online at <https://aerobasegroup.com/nsn/5930-00-296-6285>

Thread Class:

2a single mounting facility

Thread Length:

0.500 inches single mounting facility

Overall Length:

4.125 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.188 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.375 inches single actuator

Overall Diameter:

2.500 inches

Nonturn Device Radius:

0.875 inches at 12:00 o'clock

Individual Section Quantity:

4

Nonturn Device Type:

Pin at 12:00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

6 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

3.0 lowest ac voltage rating at sea level

Shaft Flat/slot Angular Location:

120.0 degrees from nonturn device single actuator

Rotor Through Connection Quantity:

1 each section

Switch Actuator Indexing Position Quantity:

6 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks 4th section rear

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

100.0 milliamperes resistive load ac at sea level and 3.0 amperes resistive load ac at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0