

View Online at <https://aerobasegroup.com/nsn/5930-00-296-6293>

Thread Class:

2a single mounting facility

Thread Length:

0.500 inches single mounting facility

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

2.891 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.214 inches single actuator and 0.217 inches single actuator

Shaft Diameter:

0.310 inches single actuator and 0.314 inches single actuator

Shaft Length:

0.375 inches single actuator

Overall Diameter:

2.625 inches

Individual Section Quantity:

1

Knob Manufacturer Code:

16764

Knob Manufacturer Part Number:

5381088

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

5 single section rear

Mounting Method:

Threaded bushing w/panel seal single mounting facility

Features Provided:

Actuator knob and metallic inclosure and push to turn

Thread Size:

0.500 inches single mounting facility

Contact Voltage Rating In Volts:

12.0 dc at sea level

Switch Actuator Indexing Position Quantity:

5 single actuator

Shaft Type:

Round, flatted, threaded hole single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Makes before breaks single section rear

Switch Actuator Positioning Increment:

25.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed-adjustable stops single actuator

Contact Load Current Rating:

15.0 amperes resistive load dc at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0