

View Online at <https://aerobasegroup.com/nsn/5930-00-296-6293>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.500 inches single mounting facility

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

2.891 inches

**First Flat Length:**

0.250 inches single actuator

**Flat Height:**

0.214 inches single actuator and 0.217 inches single actuator

**Shaft Diameter:**

0.310 inches single actuator and 0.314 inches single actuator

**Shaft Length:**

0.375 inches single actuator

**Overall Diameter:**

2.625 inches

**Individual Section Quantity:**

1

**Knob Manufacturer Code:**

16764

**Knob Manufacturer Part Number:**

5381088

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 single section rear

**Throw Quantity:**

5 single section rear

**Mounting Method:**

Threaded bushing w/panel seal single mounting facility

**Features Provided:**

Actuator knob and metallic inclosure and push to turn

**Thread Size:**

0.500 inches single mounting facility

**Contact Voltage Rating In Volts:**

12.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

5 single actuator

**Shaft Type:**

Round, flatted, threaded hole single actuator

**Terminal Type:**

Tab w/screw

**Contact Switching Action:**

Makes before breaks single section rear

**Switch Actuator Positioning Increment:**

25.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed-adjustable stops single actuator

**Contact Load Current Rating:**

15.0 amperes resistive load dc at sea level

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unf single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0