

View Online at <https://aerobasegroup.com/nsn/5930-00-296-6318>

**Body Style:**

Hole mount

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

2.250 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 1.796 inches and 1.828 inches

**Overall Height:**

2.563 inches

**Overall Width:**

0.969 inches

**Body Length:**

Between 2.219 inches and 2.281 inches

**Body Width:**

Between 0.938 inches and 1.000 inches

**Body Height:**

Between 1.594 inches and 1.656 inches

**Actuator Style:**

Round

**Actuator Height:**

Between 0.719 inches and 0.781 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained

**Maximum Voltage Rating In Volts:**

24.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.164 inches

**Nonpile-up Contact Arrangement:**

1 pole, single throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

25.000 amperes resistive dc and 15.000 amperes inductive dc and 6.000 amperes lamp dc

**Test Data Document:**

81349-mils/3735 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

2 connector, receptacle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0