

View Online at <https://aerobasegroup.com/nsn/5930-00-296-6319>

Body Style:

Hole mount

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

2.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.812 inches

Overall Height:

2.563 inches

Overall Width:

0.969 inches

Body Length:

2.250 inches

Body Width:

0.969 inches

Body Height:

1.625 inches

Actuator Style:

Round

Actuator Height:

0.750 inches

Actuator Position-action Relationship:

Up position maintained and down position momentary

Maximum Voltage Rating In Volts:

24.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Thready Qty Per Inch (tpi):

32

Thread Size:

0.164 inches

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

25.000 amperes resistive dc and 15.000 amperes inductive dc and 6.000 amperes lamp dc

Test Data Document:

81349-mil-s-13735 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Terminal Type And Quantity:

2 connector, receptacle

Specification Data:

96906-ms39061 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0