NSN 5930-00-296-6320

Hazardous Locations/environmental Protection:

Toggle Switch - Page 1 of 2

Body Style: Hole mount

Watertight



View Online at https://aerobasegroup.com/nsn/5930-00-296-6320

| Overall Length: |
|---|
| 2.250 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| Between 1.781 inches and 1.843 inches |
| Overall Height: |
| 2.405 inches |
| Overall Width: |
| 0.406 inches |
| Body Length: |
| 2.250 inches |
| Body Width: |
| Between 0.375 inches and 0.437 inches |
| Body Height: |
| 1.562 inches |
| Case Material: |
| Metal |
| Actuator Style: |
| Round |
| Actuator Height: |
| Between 0.781 inches and 0.843 inches |
| Actuator Position-action Relationship: |
| Up position maintained and down position maintained |
| Maximum Voltage Rating In Volts: |
| 24.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Unthreaded hole |
| Features Provided: |
| Actuator seal |
| Nonpile-up Contact Arrangement: |
| 1 pole, single throw, both positions maintained single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 25.000 amperes resistive dc and 15.000 amperes inductive dc and 6.000 amperes lamp dc |
| Terminal Type And Quantity: |
| 2 wire lead |
| Shelf Life: |
| N/a |
| |
| |

NSN 5930-00-296-6320 Toggle Switch - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

Demilitarization:

No

Fiig:

A053a0