# NSN 5930-00-296-6532

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-296-6532

#### **Body Style:**

Bushing mounted

#### Hazardous Locations/environmental Protection:

Waterproof

### **Body Diameter:**

0.562 inches

#### **Bushing Length:**

0.299 inches

#### **Body Length:**

0.406 inches

Case Material:

#### Metal

Actuator Height:

#### 0.188 inches

Actuator Color:

#### Red single actuator

Maximum Voltage Rating In Volts:

240.0 ac and 24.0 dc

#### Inclosure Type:

Fully enclosed

#### Mounting Method:

Threaded bushing

#### Thready Qty Per Inch (tpi):

24

#### Thread Size:

0.625 inches

#### Nonpile-up Contact Arrangement:

1 pole, double throw, double break/double make, permanent jumper, one position momentary single switch unit

#### Contact Load Current Rating At Maximum Rated Voltage:

17.000 amperes resistive dc and 7.500 amperes resistive ac

#### Precious Material And Location:

Terminals silver

#### **Thread Series Designator:**

Unef

# Terminal Type And Quantity:

4 tab, solder lug

# Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

Yes - demil/mli

# NSN 5930-00-296-6532

Push Switch - Page 2 of 2

Fiig: A053a0

