NSN 5930-00-296-7196

Hazardous Locations/environmental Protection:

Vibration resistant
Overall Length:
4.562 inches
Overall Height:
1.437 inches
Overall Width:
1.578 inches
Body Length:
3.562 inches

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-296-7196

Unthreaded Mounting Hole Diameter:
0.221 inches
Longest Vertical Distance Between Mounting Centers:
1.082 inches
Tempurature Sensing Element Type:
Expanding shell
Mounting Facility Circle Radius:
0.625 inches
Operating Tempurature Rating:
Between -100.0 degrees fahrenheit and 650.0 degrees fahrenheit
Mounting Method:
Flange and unthreaded hole
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Three position circular
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Tab w/screw
Contact Load Current Rating:
5.0 amperes resistive load first voltage
Contact Adjustability:
Actuation point adjustable, preset
Contact Adjustment Range:
-100.00/+650.00 actuation point degrees fahrenheit
Contact Adjustment Type:
External actuation point screw
Contact Stimulus Rating:
638.00 actuation point degrees fahrenheit
Contact Voltage Rating In Volts:

115.0 ac at sea level first voltage28.0 dc at sea level second voltage115.0 dc at sea level third voltage

NSN 5930-00-296-7196 Thermostatic Switch - Page 2 of 2



Media For Which Designed:
Gas or liquid
Style Designator:
Rectangular
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0