

View Online at <https://aerobasegroup.com/nsn/5930-00-296-7318>

**Hazardous Locations/environmental Protection:**

Watertight

**First Flat Length:**

0.250 inches single actuator

**Flat Height:**

0.311 inches single actuator

**Shaft Diameter:**

0.375 inches single actuator

**Shaft Length:**

0.500 inches single actuator

**Overall Diameter:**

7.500 inches

**Unthreaded Mounting Hole Diameter:**

0.406 inches single mounting facility

**Individual Section Quantity:**

3

**Knob Manufacturer Code:**

80064

**Knob Manufacturer Part Number:**

9000-S6-202-7408

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section front

**Throw Quantity:**

1 each section front

**Mounting Facility Circle Radius:**

3.312 inches single mounting facility

**Mounting Method:**

Bracket single mounting facility

**Features Provided:**

Actuator knob and metallic inclosure

**Contact Voltage Rating In Volts:**

450.0 ac at sea level

**Switch Actuator Momentary Position:**

Clockwise single actuator and counterclockwise single actuator

**Mounting Facility Pattern:**

Three position circular single mounting facility

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab w/screw

**Contact Switching Action:**

Breaks before makes each section front

**Switch Actuator Positioning Increment:**

90.0 degrees single actuator

**Contact Load Current Rating:**

30.0 amperes resistive load dc at sea level

**Test Data Document:**

80064-9000s6202-74276 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Specification Or Standard:**

3sr3a4-2 type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0