

View Online at <https://aerobasegroup.com/nsn/5930-00-296-7318>

Hazardous Locations/environmental Protection:

Watertight

First Flat Length:

0.250 inches single actuator

Flat Height:

0.311 inches single actuator

Shaft Diameter:

0.375 inches single actuator

Shaft Length:

0.500 inches single actuator

Overall Diameter:

7.500 inches

Unthreaded Mounting Hole Diameter:

0.406 inches single mounting facility

Individual Section Quantity:

3

Knob Manufacturer Code:

80064

Knob Manufacturer Part Number:

9000-S6-202-7408

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

1 each section front

Mounting Facility Circle Radius:

3.312 inches single mounting facility

Mounting Method:

Bracket single mounting facility

Features Provided:

Actuator knob and metallic inclosure

Contact Voltage Rating In Volts:

450.0 ac at sea level

Switch Actuator Momentary Position:

Clockwise single actuator and counterclockwise single actuator

Mounting Facility Pattern:

Three position circular single mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

30.0 amperes resistive load dc at sea level

Test Data Document:

80064-9000s6202-74276 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Specification Or Standard:

3sr3a4-2 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0