## NSN 5930-00-296-7413

Rotary Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-296-7413

Hazardous Locations/environmental Protection:
Dustproof
First Flat Length:
0.500 inches single actuator
Flat Height:
0.218 inches single actuator
Shaft Diameter:
0.250 inches single actuator
Shaft Length:
0.750 inches single actuator
Individual Section Quantity:
2
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 each section front
Throw Quantity:
2 each section front
Mounting Method:
Base single mounting facility
Switch Actuator Indexing Position Quantity:
Control Actuation in Control Actuality.
2 single actuator
2 single actuator
2 single actuator  Shaft Type:
2 single actuator  Shaft Type:  Round, flatted single actuator
2 single actuator  Shaft Type:  Round, flatted single actuator  Terminal Type:
2 single actuator  Shaft Type:  Round, flatted single actuator  Terminal Type:  Tab w/screw
2 single actuator  Shaft Type:  Round, flatted single actuator  Terminal Type:  Tab w/screw  Contact Switching Action:
2 single actuator  Shaft Type:  Round, flatted single actuator  Terminal Type:  Tab w/screw  Contact Switching Action:  Breaks before makes each section front
2 single actuator  Shaft Type: Round, flatted single actuator  Terminal Type: Tab w/screw  Contact Switching Action: Breaks before makes each section front  Switch Actuator Positioning Increment:
2 single actuator  Shaft Type: Round, flatted single actuator  Terminal Type: Tab w/screw  Contact Switching Action: Breaks before makes each section front  Switch Actuator Positioning Increment: 180.0 degrees single actuator
2 single actuator  Shaft Type: Round, flatted single actuator  Terminal Type: Tab w/screw  Contact Switching Action: Breaks before makes each section front  Switch Actuator Positioning Increment: 180.0 degrees single actuator  Special Features:
2 single actuator  Shaft Type: Round, flatted single actuator  Terminal Type: Tab w/screw  Contact Switching Action: Breaks before makes each section front  Switch Actuator Positioning Increment: 180.0 degrees single actuator  Special Features: Four 10-32 tapped holes spaced 90 degrees apart on 0.813 in. R}adius
2 single actuator  Shaft Type: Round, flatted single actuator  Terminal Type: Tab w/screw  Contact Switching Action: Breaks before makes each section front  Switch Actuator Positioning Increment: 180.0 degrees single actuator  Special Features: Four 10-32 tapped holes spaced 90 degrees apart on 0.813 in. R}adius  Shelf Life:
2 single actuator  Shaft Type: Round, flatted single actuator  Terminal Type: Tab w/screw  Contact Switching Action: Breaks before makes each section front  Switch Actuator Positioning Increment: 180.0 degrees single actuator  Special Features: Four 10-32 tapped holes spaced 90 degrees apart on 0.813 in. R}adius  Shelf Life: N/a
2 single actuator  Shaft Type: Round, flatted single actuator  Terminal Type: Tab w/screw  Contact Switching Action: Breaks before makes each section front  Switch Actuator Positioning Increment: 180.0 degrees single actuator  Special Features: Four 10-32 tapped holes spaced 90 degrees apart on 0.813 in. R}adius  Shelf Life: N/a
2 single actuator  Shaft Type: Round, flatted single actuator  Terminal Type: Tab w/screw  Contact Switching Action: Breaks before makes each section front  Switch Actuator Positioning Increment: 180.0 degrees single actuator  Special Features: Four 10-32 tapped holes spaced 90 degrees apart on 0.813 in. R}adius  Shelf Life: N/a  Unit Of Measure:
2 single actuator  Shaft Type: Round, flatted single actuator  Terminal Type: Tab w/screw  Contact Switching Action: Breaks before makes each section front  Switch Actuator Positioning Increment: 180.0 degrees single actuator  Special Features: Four 10-32 tapped holes spaced 90 degrees apart on 0.813 in. R}adius  Shelf Life: N/a  Unit Of Measure: Demilitarization: