# NSN 5930-00-296-7450

Lever Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-296-7450

# Body Style:

Hole mounted

# Hazardous Locations/environmental Protection:

Industrial use

# Center To Center Distance Between Mounting Facilities Parallel To Width:

0.750 inches

# Body Length:

1.094 inches

## Body Width:

1.719 inches

# Body Height:

1.875 inches

# **Unthreaded Mounting Hole Diameter:**

Between 0.108 inches and 0.112 inches

# Actuator Length:

0.626 inches

#### **Actuator Style:**

Pivoted

#### Actuator Height:

0.531 inches

### Actuator Position-action Relationship:

Up position maintained and center position maintained

# Actuator Position-locking Relationship:

Up position locked in and center position locked in and out

### Maximum Voltage Rating In Volts:

50.0 dc

#### Inclosure Type:

Uninclosed

#### **Mounting Method:**

Unthreaded hole

#### Thready Qty Per Inch (tpi):

56

# Pile-up Contact Form Arrangement:

6c single position

#### **Thread Size:**

0.099 inches

### Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc

#### **Thread Series Designator:**

Unf

### **Terminal Type And Quantity:**

18 tab, solder lug

# NSN 5930-00-296-7450

Lever Switch - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0

