## NSN 5930-00-296-9086

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-296-9086 **Body Style:** Hole mounted **Hazardous Locations/environmental Protection:** Dustproof **Case Material:** Metal **Actuator Style:** Round **Actuator Height:** 0.968 inches **Actuator Free Position Height:** 0.968 inches **Housing Height:** 1.812 inches **Housing Length:** 2.437 inches **Housing Width:** 1.000 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Width: 1.625 inches **Maximum Voltage Rating In Volts:** 600.0 ac and 250.0 dc **Inclosure Type:** Fully enclosed **Nonpile-up Contact Arrangement:** 1 pole, single throw, normally open, momentary action single switch unit **Switch Release Force:** 4.0 ounces **Switch Actuating Force:** 36.0 ounces **Actuator Movement:** Between 0.078 pretravel inches and 0.219 overtravel inches and 0.0005 differential inches **Contact Load Current Rating At Maximum Rated Voltage:** 700.000 milliamperes resistive dc and 2.000 amperes resistive ac **Terminal Type And Quantity:** 2 screw Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No

## NSN 5930-00-296-9086

Sensitive Switch - Page 2 of 2



Fiig:

A053a0