

View Online at <https://aerobasegroup.com/nsn/5930-00-296-9089>

Body Style:

Bushing/hole mounted

Overall Length:

2.062 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.984 inches and 1.016 inches

Bushing Length:

Between 0.734 inches and 0.766 inches

Body Length:

1.938 inches

Body Width:

Between 0.796 inches and 0.828 inches

Body Height:

0.844 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.296 inches and 0.328 inches

Actuator Height:

Between 0.452 inches and 0.484 inches

Actuator Free Position Height:

Between 1.952 inches and 1.984 inches

Actuator Adapter Style:

Pushbutton

Adapter Bushing Length:

Between 0.734 inches and 0.766 inches

Maximum Voltage Rating In Volts:

460.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

Between 22.0 ounces and 34.0 ounces

Actuator Movement:

Between 0.035 pretravel inches and 0.188 overtravel inches and 0.006 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

700.000 milliamperes resistive dc and 15.000 amperes resistive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0