

View Online at <https://aerobasegroup.com/nsn/5930-00-296-9089>

**Body Style:**

Bushing/hole mounted

**Overall Length:**

2.062 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.984 inches and 1.016 inches

**Bushing Length:**

Between 0.734 inches and 0.766 inches

**Body Length:**

1.938 inches

**Body Width:**

Between 0.796 inches and 0.828 inches

**Body Height:**

0.844 inches

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.296 inches and 0.328 inches

**Actuator Height:**

Between 0.452 inches and 0.484 inches

**Actuator Free Position Height:**

Between 1.952 inches and 1.984 inches

**Actuator Adapter Style:**

Pushbutton

**Adapter Bushing Length:**

Between 0.734 inches and 0.766 inches

**Maximum Voltage Rating In Volts:**

460.0 ac and 250.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action single switch unit

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

Between 22.0 ounces and 34.0 ounces

**Actuator Movement:**

Between 0.035 pretravel inches and 0.188 overtravel inches and 0.006 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

700.000 milliamperes resistive dc and 15.000 amperes resistive ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0