

View Online at <https://aerobasegroup.com/nsn/5930-00-296-9149>

**Body Style:**

Bushing/hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.000 inches

**Bushing Length:**

0.520 inches

**Body Length:**

1.937 inches

**Body Width:**

0.687 inches

**Body Height:**

0.930 inches

**Unthreaded Mounting Hole Diameter:**

0.140 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.328 inches

**Actuator Height:**

0.339 inches

**Actuator Free Position Height:**

1.500 inches

**Maximum Voltage Rating In Volts:**

600.0 ac and 230.0 dc

**Inclosure Type:**

Fully enclosed

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

Between 20.0 ounces and 28.0 ounces

**Actuator Movement:**

Between 0.040 pretravel inches and 0.219 overtravel inches and 0.010 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

300.000 milliamperes resistive dc and 100.000 milliamperes inductive dc and 300.000 milliamperes lamp dc and 100.000 milliamperes motor dc and 2.000 amperes resistive ac and 500.000 milliamperes lamp ac and 2.000 milliamperes motor ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

3 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0