

View Online at <https://aerobasegroup.com/nsn/5930-00-296-9330>

**Body Style:**

Hole mounted

**Overall Length:**

1.375 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.872 inches and 0.878 inches

**Overall Height:**

1.000 inches

**Overall Width:**

0.421 inches

**Body Length:**

1.094 inches

**Body Width:**

0.421 inches

**Body Height:**

0.625 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

Between 0.113 inches and 0.116 inches

**Actuator Length:**

0.110 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.109 inches

**Actuator Width:**

0.165 inches

**Actuator Free Position Height:**

0.219 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 285.0 dc

**End Application:**

Forrestal class cv, virginia class cgn (41), nimitz class cvn, ticonderoga class cg (47), kidd class ddg, oliver perry class ffg, spruance class dd (963). An/sps-4 (v) series radar. U-2 airframe. Deep submergence systems programs (dssp) .

**Inclosure Type:**

Fully enclosed

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

**Switch Release Force:**

2.0 ounces

**Criticality Code Justification:**

Feat

**Switch Actuating Force:**

8.0 ounces

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive dc and 10.000 amperes resistive ac

**Special Features:**

Weapon system essential

**Terminal Type And Quantity:**

3 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0