

View Online at <https://aerobasegroup.com/nsn/5930-00-296-9330>

Body Style:

Hole mounted

Overall Length:

1.375 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.872 inches and 0.878 inches

Overall Height:

1.000 inches

Overall Width:

0.421 inches

Body Length:

1.094 inches

Body Width:

0.421 inches

Body Height:

0.625 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

Between 0.113 inches and 0.116 inches

Actuator Length:

0.110 inches

Actuator Style:

Rectangular

Actuator Height:

0.109 inches

Actuator Width:

0.165 inches

Actuator Free Position Height:

0.219 inches

Maximum Voltage Rating In Volts:

250.0 ac and 285.0 dc

End Application:

Forrestal calss cv, virginia class cgn (41), nimitz class cvn, ticonderoga class cg (47), kidd class ddg, oliver perry class ffg, spruance class dd (963). An/sps-4 (v) series radar. U-2 airframe. Deep submergence systems programs (dssp) .

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

2.0 ounces

Criticality Code Justification:

Feat

Switch Actuating Force:

8.0 ounces

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 10.000 amperes resistive ac

Special Features:

Weapon system essential

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0