## NSN 5930-00-296-9333

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-296-9333

| Body Style:  |
|--|
| Hole mounted   |
| Hazardous Locations/environmental Protection:  |
| Dustproof  |
| Center To Center Distance Between Mounting Facilities Parallel To Length:                |
| 1.000 inches   |
| Body Length:   |
| 1.940 inches   |
| Body Width:  |
| 0.687 inches   |
| Body Height:   |
| 0.928 inches   |
| Unthreaded Mounting Hole Diameter:   |
| 0.140 inches   |
| Actuator Length:   |
| 1.938 inches   |
| Actuator Style:  |
| Leaf   |
| Actuator Width:  |
| 0.188 inches   |
| Actuator Free Position Height:   |
| 0.718 inches   |
| Maximum Voltage Rating In Volts:   |
| 480.0 ac   |
| Inclosure Type:  |
| Fully enclosed   |
| Mounting Method:   |
| Threaded hole  |
| Nonpile-up Contact Arrangement:  |
| 1 pole, double throw, one position momentary single switch unit                          |
| Switch Release Force:  |
| 0.5 ounces   |
| Switch Actuating Force:  |
| 4.0 ounces   |
| Actuator Movement:   |
| Between 0.094 pretravel inches and 0.031 overtravel inches and 0.015 differential inches |
| Contact Load Current Rating At Maximum Rated Voltage:                                    |
| 1.000 amperes resistive dc and 15.000 amperes resistive ac                               |
| Terminal Type And Quantity:  |
| 3 tab, solder lug  |
| Shelf Life:  |
| N/a  |

## NSN 5930-00-296-9333

Sensitive Switch - Page 2 of 2



|   | 1  | :. | ~  | 84  |    |    |      |   |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A053a0