## NSN 5930-00-296-9336

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-296-9336
Body Style:
Hole mounted
Overall Length:
1.938 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
Between 0.998 inches and 1.002 inches
Overall Width:
0.688 inches
Body Length:
1.938 inches
Body Width:
0.688 inches
Body Height:
1.047 inches
Unthreaded Mounting Hole Diameter:
Between 0.139 inches and 0.140 inches
Actuator Length:
0.734 inches
Actuator Style:
Roller arm
Actuator Free Position Height:

1.250 inches

**Actuator Roller Diameter:** 

0.375 inches

**Actuator Roller Width:** 

0.156 inches

**Maximum Voltage Rating In Volts:** 

460.0 ac and 250.0 dc

**Inclosure Type:** 

Fully enclosed

**Mounting Method:** 

Threaded hole

**Nonpile-up Contact Arrangement:** 

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:** 

6.02 ounces

**Switch Actuating Force:** 

19.02 ounces

**Actuator Movement:** 

Between 0.109 pretravel inches and 0.078 overtravel inches and 0.011 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:** 

250.000 milliamperes resistive dc and 15.000 amperes resistive ac and 7.500 amperes inductive ac

## NSN 5930-00-296-9336

Sensitive Switch - Page 2 of 2



Terminal Type Ar	nd Quantity:
------------------	--------------

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0